

## OFYX™ Fiber optic cable Single-mode OS2, Outdoor, 8 core, Single Tube, CM, Armoured, Corrugated steel

MODEL NUMBER : FCOFYX-SM2S2ACS008F



### Specifications :

| Product Classification         |                                      |
|--------------------------------|--------------------------------------|
| Regional Availability          | Asia   Europe   Middle East   Africa |
| Portfolio                      | OFYX®                                |
| Product Type                   | Fiber outdoor cable                  |
| Product Series                 | SM Fiber                             |
| General Specifications         |                                      |
| Subunit Type                   | Gel-free                             |
| Cable Type                     | Single Tube                          |
| Construction Type <sup>1</sup> | Corrugated steel armour              |
| Application                    | Direct Buried   Duct                 |
| Environment                    | Outdoor                              |
| Cable Design                   |                                      |
| Fiber Count                    | 8                                    |
| Number of ripcords             | 2 ripcords                           |
| Fibre colouring                | Blue-orange-green-brown-grey-white   |
| Fiber per tube                 | 8F                                   |

|                                            |                                                           |
|--------------------------------------------|-----------------------------------------------------------|
| Outer jacket colour                        | Black.                                                    |
| Outer jacket material                      | Linear Low Density Polyethylene (LLDPE)                   |
| Tape                                       | Water-swellable                                           |
| Tensile strength elements and/or armouring | Corrugated steel tape armour                              |
| Mechanical Specifications                  |                                                           |
| Minimum Bend Radius, operation             | 85 mm                                                     |
| Nominal outer diameter                     | 8.5 mm                                                    |
| Max. tensile strength for installation     | 2700 N                                                    |
| Crush resistance                           | 2000 N/10 cm                                              |
| Minimum Bend Radius, installation          | 170 mm                                                    |
| Optical Specifications                     |                                                           |
| Fibre category                             | OS2                                                       |
| Cable cutoff wavelength                    | 1260 nm                                                   |
| Fibre name                                 | OFYX                                                      |
| Fibre compliance                           | ITU-T G.652.D and ITU-T G.657.A1                          |
| Dispersion @ 1550 nm                       | 18 nm                                                     |
| Dispersion @ 1625 nm                       | 22 nm                                                     |
| Maximum Attenuation                        | 0.34 dB/km / 0.34 dB/km / 0.20 dB/km                      |
| Wavelengths                                | 1310 nm / 1383 nm / 1550 nm                               |
| Fibre Type                                 | Single-mode                                               |
| Environmental Specifications               |                                                           |
| Temperature range, installation            | -5 °C to 50 °C                                            |
| Temperature range, operation               | -20 °C to 60 °C                                           |
| Temperature range, storage                 | -25 °C to 70 °C                                           |
| Regulatory Compliance/Certifications       |                                                           |
| ROHS                                       | Free of hazardous substances according to RoHS 2011/65/EU |

|                        |                |
|------------------------|----------------|
| Approvals and Listings | IEC 60794-3-11 |
| Waterblocking          | IEC 60794-1-2  |