

## AMP CONNECT® THUNDER X10® Copper Patch cord Max Easy, UTP, Cat6A, 26AWG, LSZH Rated,Black, 15 Meter

MODEL NUMBER : CCTHX10-ULE15BK



### Specifications :

| Produkt Klassifikation   |                                      |
|--------------------------|--------------------------------------|
| Regional Availability    | Asia   Europe   Middle East   Africa |
| Portfolio                | THUNDER X10®                         |
| Product Type             | Twisted pair patch cord              |
| Product Series           | MAX EASY                             |
| Allgemeine Spezifikation |                                      |
| ANSI/TIA Category        | Cat 6A                               |
| Cable Type               | U/UTP (unshielded)                   |
| Jacket Color             | Black.                               |
| Conductor Type           | Stranded                             |
| Transmission Standards   | IEEE 802.3bt Type 4                  |
| Interface, Connector A   | RJ45 plug.                           |
| Interface, Connector B   | RJ45 plug                            |
| Pairs Quantity           | 4 Pairs                              |

|                                      |                                                                                 |
|--------------------------------------|---------------------------------------------------------------------------------|
| Wiring                               | T568B                                                                           |
| Compatible Conductor Gauge, stranded | 24 AWG                                                                          |
| Material Specifications              |                                                                                 |
| Contact Plating Material             | Precious metals                                                                 |
| Material Type                        | Copper alloy   Polycarbonate                                                    |
| Mechanical Specifications            |                                                                                 |
| Plug Insertion Life, minimum         | 750 times                                                                       |
| Plug Retention Force, minimum        | 133 N   29.9 lbf                                                                |
| Environmental Specifications         |                                                                                 |
| Operating Temperature                | -10 °C to +60 °C (+14 °F to +140 °F)                                            |
| Environmental Space                  | Polyvinyl Chloride (PVC)                                                        |
| Flammability Rating                  | UL 94 V-2                                                                       |
| Dimensions                           |                                                                                 |
| Diameter Over Jacket                 | 6.02 mm                                                                         |
| Cable Assembly Length (m)            | 15.                                                                             |
| Cable Assembly Length (ft)           | 50                                                                              |
| Wiring Diagram                       | 0                                                                               |
| Regulatory Compliance/Certifications |                                                                                 |
| ISO 9001:2015                        | Designed - manufactured and/or distributed under this quality management system |
| Packing                              |                                                                                 |
| Packaging quantity                   | 1PC                                                                             |