

## 19" 1U 3 WAY FRENCH TYPE NFC 61314 SOCKET WITH CURRENT AND VOLTAGE DISPLAY CIRCUIT BREAKER , 3X1,5 mm<sup>2</sup> NYMHY CABLE, DIN49441 PLUG ALUMINIUM PROFILE FRAME POWER DISTRIBUTION UNIT

MODEL NUMBER : **GH191203132**



### Specifications :

Produkt Klassifikation	
Regional Availability	Asia   Europe   Middle East   Africa
Product Type	Basic PDU
Product Series	Note0
INPUT Characteristics	
PDU Input Voltage	220V AC - 250V AC
Maximum Input Amps	16A
PDU Plug Type	F Type Plug
Input Cord Length (m)	1.5
Input Cord Length (ft.)	5.
Cable Specefications	3x1.5mm <sup>2</sup> NYMHY(16AWG)
Protection Control	Miniature Circuit Breaker
Control Function	Multimeter&Circuit Breaker

Input Phase	Single Phase
<b>AUSGABE-Merkmale</b>	
Output Load Capacity	250V AC 16A / 4kVA
Frequency Compatibility	50 / 60 Hz
1. Type of Sockets	French Socket
1. Sockets Qty.	3
<b>Cable Design</b>	
REACH Regulation	REACH Declaration
Product Certifications	CE
REACH Free of SVCH	Yes
EU RoHS Directive	Compliant   EU RoHS Declaration
Mercury Free	Yes.
China RoHS Regulation	China RoHS Declaration
<b>Mechanical Specifications</b>	
Rack Unit	1U.
Mounting Position	Horizontal
Mounting Location	Front
Material & Colour	Aluminum Anodizing
Depth	44.45mm.
Height	44.45mm
Weight	0.90 Kg.
Widht	482.6mm(19")
<b>Environmental Specifications</b>	
Operating Temperature	23 F° - 140 F° (-5C° - 60C°)
Storage Temperature	-13 F° - 149 F° (-25C° - 65C°)
Relative Humidity	%5 - %95
Operating Elevation (ft.)	0ft. - 100000ft.
<b>Regulatory Compliance/Certifications</b>	
RoHS Exemption Information	Yes..
WEEE	Note11

Standards	IEC 62368-1
<b>Packing</b>	
Packaging quantity	1PC