

**19" 2U 9 WAY BRITISH TYPE BS1363  
SOCKET CIRCUIT BREAKER AND SURGE  
PROTECTION DEVICE CONNECTED, 3X1,5  
mm² NYMHY CABLE, C14 PLUG ALUMINIUM  
PROFILE FRAME POWER DISTRIBUTION  
UNIT**

MODEL NUMBER : **CPH192309132**



Specifications :

| Clasificación del producto |                                                                             |
|----------------------------|-----------------------------------------------------------------------------|
| Regional Availability      | Asia   Europe   Middle East   Africa , Asia   Europe   Middle East   Africa |
| Product Type               | Basic PDU , Basic PDU                                                       |
| Product Series             | Note0 , Note0                                                               |
| INPUT Characteristics      |                                                                             |
| PDU Input Voltage          | 220V AC - 250V AC , 220V AC - 250V AC                                       |
| Maximum Input Amps         | 10A , 10A                                                                   |
| PDU Plug Type              | C14 Type Plug , C14 Type Plug                                               |
| Input Cord Length (m)      | 1.5 , 1.5                                                                   |
| Input Cord Length (ft.)    | 5. , 5.                                                                     |
| Cable Specefications       | 3x1.5mm² NYMHY(16AWG) , 3x1.5mm² NYMHY(16AWG)                               |
| Protection Control         | SPD&MCB , SPD&MCB                                                           |
| Control Function           | SPD Light&Circuit Breaker , SPD Light&Circuit Breaker                       |

|                                             |                                                                   |
|---------------------------------------------|-------------------------------------------------------------------|
| Input Phase                                 | Single Phase , Single Phase                                       |
| <b>Características de SALIDA</b>            |                                                                   |
| Output Load Capacity                        | 250V AC 10A / 2.5kVA , 250V AC 10A / 2.5kVA                       |
| Frequency Compatibility                     | 50 / 60 Hz , 50 / 60 Hz                                           |
| 1. Type of Sockets                          | BS1363 UK Socket , BS1363 UK Socket                               |
| 1. Sockets Qty.                             | 9 , 9                                                             |
| <b>Cable Design</b>                         |                                                                   |
| REACH Regulation                            | REACH Declaration , REACH Declaration                             |
| Product Certifications                      | CE , CE                                                           |
| REACH Free of SVCH                          | Yes , Yes                                                         |
| EU RoHS Directive                           | Compliant   EU RoHS Declaration , Compliant   EU RoHS Declaration |
| Mercury Free                                | Yes. , Yes.                                                       |
| China RoHS Regulation                       | China RoHS Declaration , China RoHS Declaration                   |
| <b>Mechanical Specifications</b>            |                                                                   |
| Rack Unit                                   | 2U. , 2U.                                                         |
| Mounting Position                           | Horizontal , Horizontal                                           |
| Mounting Location                           | Front , Front                                                     |
| Material & Colour                           | Aluminum Anodizing , Aluminum Anodizing                           |
| Depth                                       | 44.45mm. , 44.45mm.                                               |
| Height                                      | 88.90mm , 88.90mm                                                 |
| Widht                                       | 482.6mm(19") , 482.6mm(19")                                       |
| <b>Environmental Specifications</b>         |                                                                   |
| Operating Temperature                       | 23 F° - 140 F° (-5C° - 60C°) , 23 F° - 140 F° (-5C° - 60C°)       |
| Storage Temperature                         | -13 F° - 149 F° (-25C° - 65C°) , -13 F° - 149 F° (-25C° - 65C°)   |
| Relative Humidity                           | %5 - %95 , %5 - %95                                               |
| Operating Elevation (ft.)                   | 0ft. - 100000ft. , 0ft. - 100000ft.                               |
| <b>Regulatory Compliance/Certifications</b> |                                                                   |
| RoHS Exemption Information                  | Yes.. , Yes..                                                     |
| WEEE                                        | Note11 , Note11                                                   |
| Standards                                   | IEC 62368-1 , IEC 62368-1                                         |

| Packing            |           |
|--------------------|-----------|
| Packaging quantity | 1PC , 1PC |