

19" 1U 6 WAY IEC320 C13 SOCKET CIRCUIT
BREAKER AND SURGE PROTECTION
DEVICE CONNECTED, 3X1,5 mm² NYMHY
CABLE, BS1363 PLUG ALUMINIUM PROFILE
FRAME POWER DISTRIBUTION UNIT

MODEL NUMBER : **IPH191406132**



Specifications :

Clasificación del producto	
Regional Availability	Asia Europe Middle East Africa
Product Type	Basic PDU
Product Series	Note0
INPUT Characteristics	
PDU Input Voltage	220V AC - 250V AC
Maximum Input Amps	13A
PDU Plug Type	UK Type Plug
Input Cord Length (m)	1.5
Input Cord Length (ft.)	5.
Cable Specefications	3x1.5mm² NYMHY(16AWG)
Protection Control	SPD&MCB
Control Function	SPD Light&Circuit Breaker
Input Phase	Single Phase

Características de SALIDA	
Output Load Capacity	250V AC 13A / 3.25kVA
Frequency Compatibility	50 / 60 Hz
1. Type of Sockets	IEC320 C13 Socket
1. Sockets Qty.	6
Cable Design	
REACH Regulation	REACH Declaration
Product Certifications	CE
REACH Free of SVCH	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury Free	Yes.
China RoHS Regulation	China RoHS Declaration
Mechanical Specifications	
Rack Unit	1U.
Mounting Position	Horizontal
Mounting Location	Front
Material & Colour	Aluminum Anodizing
Depth	44.45mm.
Height	44.45mm
Widht	482.6mm(19")
Environmental Specifications	
Operating Temperature	23 F° - 140 F° (-5C° - 60C°)
Storage Temperature	-13 F° - 149 F° (-25C° - 65C°)
Relative Humidity	%5 - %95
Operating Elevation (ft.)	0ft. - 100000ft.
Regulatory Compliance/Certifications	
RoHS Exemption Information	Yes..
WEEE	Note11
Standards	IEC 62368-1
Packing	

Packaging quantity	1PC
--------------------	-----