

## AMP Connect® 19" Basic PDU Series, 19", 1U, 8 UK Socket, 1 Phase, 250V AC, 13A, 1,5m 3x1,5mm² NYMHY Cable, F Type Plug

MODEL NUMBER : **SIH191308130**

### Specifications :

| Clasificación del producto |                                      |
|----------------------------|--------------------------------------|
| Regional Availability      | Asia   Europe   Middle East   Africa |
| Product Type               | Basic PDU                            |
| Product Series             | Note0                                |
| INPUT Characteristics      |                                      |
| PDU Input Voltage          | 220V AC - 250V AC                    |
| Maximum Input Amps         | 16A                                  |
| PDU Plug Type              | F Type Plug                          |
| Input Cord Length (m)      | 1.5                                  |
| Input Cord Length (ft.)    | 5.                                   |
| Cable Specefications       | 3x1.5mm² NYMHY(16AWG)                |
| Protection Control         | Direct Connected                     |
| Control Function           | Direct Connected.                    |
| Input Phase                | Single Phase                         |
| Características de SALIDA  |                                      |
| Output Load Capacity       | 250V AC 16A / 4kVA                   |
| Frequency Compatibility    | 50 / 60 Hz                           |
| 1. Type of Sockets         | BS1363 UK Socket                     |
| 1. Sockets Qty.            | 8                                    |
| Cable Design               |                                      |
| REACH Regulation           | REACH Declaration                    |
| Product Certifications     | CE                                   |
| REACH Free of SVCH         | Yes                                  |
| EU RoHS Directive          | Compliant   EU RoHS Declaration      |

|                                             |                                |
|---------------------------------------------|--------------------------------|
| Mercury Free                                | Yes.                           |
| China RoHS Regulation                       | China RoHS Declaration         |
| <b>Mechanical Specifications</b>            |                                |
| Rack Unit                                   | 1U.                            |
| Mounting Position                           | Horizontal                     |
| Mounting Location                           | Front                          |
| Material & Colour                           | Aluminum Anodizing             |
| Depth                                       | 44.45mm.                       |
| Height                                      | 44.45mm                        |
| Widht                                       | 482.6mm(19")                   |
| <b>Environmental Specifications</b>         |                                |
| Operating Temperature                       | 23 F° - 140 F° (-5C° - 60C°)   |
| Storage Temperature                         | -13 F° - 149 F° (-25C° - 65C°) |
| Relative Humidity                           | %5 - %95                       |
| Operating Elevation (ft.)                   | 0ft. - 100000ft.               |
| <b>Regulatory Compliance/Certifications</b> |                                |
| RoHS Exemption Information                  | Yes..                          |
| WEEE                                        | Note11                         |
| Standards                                   | IEC 62368-1                    |
| <b>Packing</b>                              |                                |
| Packaging quantity                          | 1PC                            |