

**19" 1U 3 BRITISH TYPE BS1363 SOCKET ON /  
OFF LIGHTED SWITCH AND SURGE  
PROTECTION DEVICE CONNECTED, 3X1,5  
mm² NYMHY CABLE, DIN49441 PLUG  
ALUMINIUM PROFILE ALUMINIUM PROFILE  
FRAME POWER DISTRIBUTION UNIT**

MODEL NUMBER : **SPH191303131**



Specifications :

| Clasificación del producto |                                      |
|----------------------------|--------------------------------------|
| Regional Availability      | Asia   Europe   Middle East   Africa |
| Product Type               | Basic PDU                            |
| Product Series             | Note0                                |
| INPUT Characteristics      |                                      |
| PDU Input Voltage          | 220V AC - 250V AC                    |
| Maximum Input Amps         | 16A                                  |
| PDU Plug Type              | F Type Plug                          |
| Input Cord Length (m)      | 1.5                                  |
| Input Cord Length (ft.)    | 5.                                   |
| Cable Specefications       | 3x1.5mm² NYMHY(16AWG)                |

|                              |                                 |
|------------------------------|---------------------------------|
| Protection Control           | Surge Protection Device         |
| Control Function             | SPD Light&On-Off Switch         |
| Input Phase                  | Single Phase                    |
| Características de SALIDA    |                                 |
| Output Load Capacity         | 250V AC 16A / 4kVA              |
| Frequency Compatibility      | 50 / 60 Hz                      |
| 1. Type of Sockets           | BS1363 UK Socket                |
| 1. Sockets Qty.              | 3                               |
| Cable Design                 |                                 |
| REACH Regulation             | REACH Declaration               |
| Product Certifications       | CE                              |
| REACH Free of SVCH           | Yes                             |
| EU RoHS Directive            | Compliant   EU RoHS Declaration |
| Mercury Free                 | Yes.                            |
| China RoHS Regulation        | China RoHS Declaration          |
| Mechanical Specifications    |                                 |
| Rack Unit                    | 1U.                             |
| Mounting Position            | Horizontal                      |
| Mounting Location            | Front                           |
| Material & Colour            | Aluminum Anodizing              |
| Depth                        | 44.45mm.                        |
| Height                       | 44.45mm                         |
| Widht                        | 482.6mm(19")                    |
| Environmental Specifications |                                 |
| Operating Temperature        | 23 F° - 140 F° (-5C° - 60C°)    |
| Storage Temperature          | -13 F° - 149 F° (-25C° - 65C°)  |
| Relative Humidity            | %5 - %95                        |

|                                      |                  |
|--------------------------------------|------------------|
| Operating Elevation (ft.)            | 0ft. - 100000ft. |
| Regulatory Compliance/Certifications |                  |
| RoHS Exemption Information           | Yes..            |
| WEEE                                 | Note11           |
| Standards                            | IEC 62368-1      |
| Packing                              |                  |
| Packaging quantity                   | 1PC              |