

19" 1U 10 WAY IEC320 C13 SOCKET, 3X1,5  
mm² NYMHY CABLE, BS1363 (UK TYPE)  
PLUG ALUMINIUM PROFILE FRAME POWER  
DISTRIBUTION UNIT

MODEL NUMBER : IH191410130



Specifications :

| Classement du produit      |                                      |
|----------------------------|--------------------------------------|
| Regional Availability      | Asia   Europe   Middle East   Africa |
| Product Type               | Basic PDU                            |
| Product Series             | Note0                                |
| INPUT Characteristics      |                                      |
| PDU Input Voltage          | 220V AC - 250V AC                    |
| Maximum Input Amps         | 13A                                  |
| PDU Plug Type              | UK Type Plug                         |
| Input Cord Length (m)      | 1.5                                  |
| Input Cord Length (ft.)    | 5.                                   |
| Cable Specefications       | 3x1.5mm² NYMHY(16AWG)                |
| Protection Control         | Direct Connected                     |
| Control Function           | Direct Connected.                    |
| Input Phase                | Single Phase                         |
| Caractéristiques de SORTIE |                                      |

|                                             |                                 |
|---------------------------------------------|---------------------------------|
| Output Load Capacity                        | 250V AC 13A / 3.25kVA           |
| Frequency Compatibility                     | 50 / 60 Hz                      |
| 1. Type of Sockets                          | IEC320 C13 Socket               |
| 1. Sockets Qty.                             | 10                              |
| <b>Cable Design</b>                         |                                 |
| REACH Regulation                            | REACH Declaration               |
| Product Certifications                      | CE                              |
| REACH Free of SVCH                          | Yes                             |
| EU RoHS Directive                           | Compliant   EU RoHS Declaration |
| Mercury Free                                | Yes.                            |
| China RoHS Regulation                       | China RoHS Declaration          |
| <b>Mechanical Specifications</b>            |                                 |
| Rack Unit                                   | 1U.                             |
| Mounting Position                           | Horizontal                      |
| Mounting Location                           | Front                           |
| Material & Colour                           | Aluminum Anodizing              |
| Depth                                       | 44.45mm.                        |
| Height                                      | 44.45mm                         |
| Widht                                       | 482.6mm(19")                    |
| <b>Environmental Specifications</b>         |                                 |
| Operating Temperature                       | 23 F° - 140 F° (-5C° - 60C°)    |
| Storage Temperature                         | -13 F° - 149 F° (-25C° - 65C°)  |
| Relative Humidity                           | %5 - %95                        |
| Operating Elevation (ft.)                   | 0ft. - 100000ft.                |
| <b>Regulatory Compliance/Certifications</b> |                                 |
| RoHS Exemption Information                  | Yes..                           |
| WEEE                                        | Note11                          |
| Standards                                   | IEC 62368-1                     |
| <b>Packing</b>                              |                                 |
| Packaging quantity                          | 1PC                             |

