

**19" 2U 8 WAY BRITISH TYPE BS1363  
SOCKET WITH CURRENT AND VOLTAGE  
DISPLAY , 3X1,5 mm² NYMHY CABLE, C20  
PLUG ALUMINIUM PROFILE FRAME POWER  
DISTRIBUTION UNIT**

MODEL NUMBER : **JGH192308130**



Specifications :

| Classement du produit   |                                                                             |
|-------------------------|-----------------------------------------------------------------------------|
| Regional Availability   | Asia   Europe   Middle East   Africa , Asia   Europe   Middle East   Africa |
| Product Type            | Basic PDU , Basic PDU                                                       |
| Product Series          | Note0 , Note0                                                               |
| INPUT Characteristics   |                                                                             |
| PDU Input Voltage       | 220V AC - 250V AC , 220V AC - 250V AC                                       |
| Maximum Input Amps      | 16A , 16A                                                                   |
| PDU Plug Type           | C20 Type Plug , C20 Type Plug                                               |
| Input Cord Length (m)   | 1.5 , 1.5                                                                   |
| Input Cord Length (ft.) | 5. , 5.                                                                     |
| Cable Specefications    | 3x1.5mm² NYMHY(16AWG) , 3x1.5mm² NYMHY(16AWG)                               |
| Protection Control      | Direct Connected , Direct Connected                                         |
| Control Function        | Multimeter , Multimeter                                                     |
| Input Phase             | Single Phase , Single Phase                                                 |

| Caractéristiques de SORTIE           |                                                                   |
|--------------------------------------|-------------------------------------------------------------------|
| Output Load Capacity                 | 250V AC 16A / 4kVA , 250V AC 16A / 4kVA                           |
| Frequency Compatibility              | 50 / 60 Hz , 50 / 60 Hz                                           |
| 1. Type of Sockets                   | BS1363 UK Socket , BS1363 UK Socket                               |
| 1. Sockets Qty.                      | 8 , 8                                                             |
| Cable Design                         |                                                                   |
| REACH Regulation                     | REACH Declaration , REACH Declaration                             |
| Product Certifications               | CE , CE                                                           |
| REACH Free of SVCH                   | Yes , Yes                                                         |
| EU RoHS Directive                    | Compliant   EU RoHS Declaration , Compliant   EU RoHS Declaration |
| Mercury Free                         | Yes. , Yes.                                                       |
| China RoHS Regulation                | China RoHS Declaration , China RoHS Declaration                   |
| Mechanical Specifications            |                                                                   |
| Rack Unit                            | 2U. , 2U.                                                         |
| Mounting Position                    | Horizontal , Horizontal                                           |
| Mounting Location                    | Front , Front                                                     |
| Material & Colour                    | Aluminum Anodizing , Aluminum Anodizing                           |
| Depth                                | 44.45mm. , 44.45mm.                                               |
| Height                               | 88.90mm , 88.90mm                                                 |
| Widht                                | 482.6mm(19") , 482.6mm(19")                                       |
| Environmental Specifications         |                                                                   |
| Operating Temperature                | 23 F° - 140 F° (-5C° - 60C°) , 23 F° - 140 F° (-5C° - 60C°)       |
| Storage Temperature                  | -13 F° - 149 F° (-25C° - 65C°) , -13 F° - 149 F° (-25C° - 65C°)   |
| Relative Humidity                    | %5 - %95 , %5 - %95                                               |
| Operating Elevation (ft.)            | 0ft. - 100000ft. , 0ft. - 100000ft.                               |
| Regulatory Compliance/Certifications |                                                                   |
| RoHS Exemption Information           | Yes.. , Yes..                                                     |
| WEEE                                 | Note11 , Note11                                                   |
| Standards                            | IEC 62368-1 , IEC 62368-1                                         |
| Packing                              |                                                                   |

|                    |           |
|--------------------|-----------|
| Packaging quantity | 1PC , 1PC |
|--------------------|-----------|