

19" 2U 15 WAY FRENCH TYPE NFC 61314  
SOCKET CIRCUIT BREAKER CONNECTED,  
3X1,5 mm² NYMHY CABLE, DIN49441 PLUG  
ALUMINIUM PROFILE FRAME POWER  
DISTRIBUTION UNIT

MODEL NUMBER : SH192215132



Specifications :

| Classement du produit   |                                      |
|-------------------------|--------------------------------------|
| Regional Availability   | Asia   Europe   Middle East   Africa |
| Product Type            | Basic PDU                            |
| Product Series          | Note0                                |
| INPUT Characteristics   |                                      |
| PDU Input Voltage       | 220V AC - 250V AC                    |
| Maximum Input Amps      | 16A                                  |
| PDU Plug Type           | F Type Plug                          |
| Input Cord Length (m)   | 1.5                                  |
| Input Cord Length (ft.) | 5.                                   |
| Cable Specefications    | 3x1.5mm² NYMHY(16AWG)                |
| Protection Control      | Miniature Circuit Breaker            |
| Control Function        | Circuit Breaker                      |
| Input Phase             | Single Phase                         |

| Caractéristiques de SORTIE           |                                 |
|--------------------------------------|---------------------------------|
| Output Load Capacity                 | 250V AC 16A / 4kVA              |
| Frequency Compatibility              | 50 / 60 Hz                      |
| 1. Type of Sockets                   | French Socket                   |
| 1. Sockets Qty.                      | 15                              |
| Cable Design                         |                                 |
| REACH Regulation                     | REACH Declaration               |
| Product Certifications               | CE                              |
| REACH Free of SVCH                   | Yes                             |
| EU RoHS Directive                    | Compliant   EU RoHS Declaration |
| Mercury Free                         | Yes.                            |
| China RoHS Regulation                | China RoHS Declaration          |
| Mechanical Specifications            |                                 |
| Rack Unit                            | 2U.                             |
| Mounting Position                    | Horizontal                      |
| Mounting Location                    | Front                           |
| Material & Colour                    | Aluminum Anodizing              |
| Depth                                | 44.45mm.                        |
| Height                               | 88.90mm                         |
| Weight                               | 1.70 Kg.                        |
| Widht                                | 482.6mm(19")                    |
| Environmental Specifications         |                                 |
| Operating Temperature                | 23 F° - 140 F° (-5C° - 60C°)    |
| Storage Temperature                  | -13 F° - 149 F° (-25C° - 65C°)  |
| Relative Humidity                    | %5 - %95                        |
| Operating Elevation (ft.)            | 0ft. - 100000ft.                |
| Regulatory Compliance/Certifications |                                 |
| RoHS Exemption Information           | Yes..                           |
| WEEE                                 | Note11                          |
| Standards                            | IEC 62368-1                     |

**Packing**

Packaging quantity

1PC