


AMP CONNECT® THUNDER X1® Copper Patch cord Max EASY, UTP, Cat6, 24AWG, LSZH Rated,Black, 15 Meter

MODEL NUMBER : **CCTHX1-ULE15BK**



Specifications :

| Product Classification | |
|------------------------|--------------------------------------|
| Regional Availability | Asia Europe Middle East Africa |
| Portfolio | THUNDER X1® |
| Product Type | Twisted pair patch cord |
| Product Series | MAX EASY |
| General Specifications | |
| ANSI/TIA Category | Cat 6 |
| Cable Type | U/UTP (unshielded) |
| Jacket Color | Black. |
| Conductor Type | Stranded |
| Transmission Standards | IEEE 802.3bt Type 4 |
| Interface, Connector A | RJ45 plug. |
| Interface, Connector B | RJ45 plug |
| Pairs Quantity | 4 Pairs |

| | |
|---|---|
| Wiring | T568B |
| Compatible Conductor Gauge, stranded | 24 AWG |
| Material Specifications | |
| Contact Plating Material | Precious metals |
| Material Type | Copper alloy Polycarbonate |
| Mechanical Specifications | |
| Plug Insertion Life, minimum | 750 times |
| Plug Retention Force, minimum | 133 N 29.9 lbf |
| Environmental Specifications | |
| Operating Temperature | -10 °C to +60 °C (+14 °F to +140 °F) |
| Environmental Space | Polyvinyl Chloride (PVC) |
| Flammability Rating | UL 94 V-2 |
| Dimensions | |
| Diameter Over Jacket | 6.02 mm |
| Cable Assembly Length (m) | 15. |
| Cable Assembly Length (ft) | 50 |
| Wiring Diagram | 0 |
| Regulatory Compliance/Certifications | |
| ISO 9001:2015 | Designed - manufactured and/or distributed under this quality management system |
| Packing | |
| Packaging quantity | 1PC |