

19" 2U 8 WAY BRITISH TYPE BS1363 SOCKET WITH CURRENT AND VOLTAGE DISPLAY , 3X1,5 mm² NYMHY CABLE, C14 PLUG ALUMINIUM PROFILE FRAME POWER DISTRIBUTION UNIT

MODEL NUMBER : **CGH192308130**



Specifications :

| Product Classification | |
|-------------------------|---|
| Regional Availability | Asia Europe Middle East Africa , Asia Europe Middle East Africa |
| Product Type | Basic PDU , Basic PDU |
| Product Series | Note0 , Note0 |
| INPUT Characteristics | |
| PDU Input Voltage | 220V AC - 250V AC , 220V AC - 250V AC |
| Maximum Input Amps | 10A , 10A |
| PDU Plug Type | C14 Type Plug , C14 Type Plug |
| Input Cord Length (m) | 1.5 , 1.5 |
| Input Cord Length (ft.) | 5. , 5. |
| Cable Specifications | 3x1.5mm ² NYMHY(16AWG) , 3x1.5mm ² NYMHY(16AWG) |
| Protection Control | Direct Connected , Direct Connected |

| | |
|------------------------------|---|
| Control Function | Multimeter , Multimeter |
| Input Phase | Single Phase , Single Phase |
| OUTPUT Characteristics | |
| Output Load Capacity | 250V AC 10A / 2.5kVA , 250V AC 10A / 2.5kVA |
| Frequency Compatibility | 50 / 60 Hz , 50 / 60 Hz |
| 1. Type of Sockets | BS1363 UK Socket , BS1363 UK Socket |
| 1. Sockets Qty. | 8 , 8 |
| Cable Design | |
| REACH Regulation | REACH Declaration , REACH Declaration |
| Product Certifications | CE , CE |
| REACH Free of SVCH | Yes , Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration , Compliant EU RoHS Declaration |
| Mercury Free | Yes. , Yes. |
| China RoHS Regulation | China RoHS Declaration , China RoHS Declaration |
| Mechanical Specifications | |
| Rack Unit | 2U. , 2U. |
| Mounting Position | Horizontal , Horizontal |
| Mounting Location | Front , Front |
| Material & Colour | Aluminum Anodizing , Aluminum Anodizing |
| Depth | 44.45mm. , 44.45mm. |
| Height | 88.90mm , 88.90mm |
| Widht | 482.6mm(19") , 482.6mm(19") |
| Environmental Specifications | |
| Operating Temperature | 23 F° - 140 F° (-5C° - 60C°), 23 F° - 140 F° (-5C° - 60C°) |
| Storage Temperature | -13 F° - 149 F° (-25C° - 65C°), -13 F° - 149 F° (-25C° - 65C°) |
| Relative Humidity | %5 - %95 , %5 - %95 |
| Operating Elevation (ft.) | 0ft. - 100000ft. , 0ft. - 100000ft. |

| Regulatory Compliance/Certifications | |
|--------------------------------------|---------------------------|
| RoHS Exemption Information | Yes.. , Yes.. |
| WEEE | Note11 , Note11 |
| Standards | IEC 62368-1 , IEC 62368-1 |
| Packing | |
| Packaging quantity | 1PC , 1PC |