

## AMP CONNECT® THUNDER X10® Max Easy Keystone Module, Shielded, Cat6A, Unshuttered, Blue

MODEL NUMBER : **CMTHX10-ESUSBL**

### Specifications :

Product Classification	
Regional Availability	Asia   Europe   Middle East   Africa
Portfolio	THUNDER X1®
Product Type	Modular jack
Product Series	EASY
General Specifications	
ANSI/TIA Category	Cat 6A
Cable Type	Shielded
Conductor Type	Solid   Stranded
Transmission Standards	ANSI/TIA-568.2-D   ISO/IEC 11801 Class EA
Wiring	T568A   T568B
Compatible Conductor Gauge, stranded	26-24
Termination Type	Tool Less
Outlet Type	Standard
Integrated Dust Cover Type	NO
Compatible Conductor Gauge, solid	24-22 AWG
Color	Blue
Material Specifications	
Contact Plating Material	Gold
Material Type	Polycarbonate   Zamak
Termination Contact Plating	Tin
Electrical Specifications	
Insulation Resistance, minimum	500 MOhm

Dielectric Withstand Voltage, RMS, conductive surface	1500 Vac at 60 Hz
Current Rating at Temperature	1.5 A at 20 °C   1.5 A at 68 °F
Contact Resistance, maximum	100 mOhm
Contact Resistance Variation, maximum	20 mOhm
<b>Environmental Specifications</b>	
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Flammability Rating	UL 94 V-2
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Safety Standard.	UL   eTL
<b>Dimensions</b>	
Width	16.8
Height.	19.6
Depth.	42.5
<b>Packing</b>	
Packaging quantity	1PC