

## AMP CONNECT® THUNDER X10® Max Easy Keystone Module, UTP, Cat6A, Shutterred, Red

MODEL NUMBER : **CMTHX10-EUSSRD**

### Specifications :

| Product Classification               |   |
|--------------------------------------|---|
| Regional Availability                | Asia   Europe   Middle East   Africa      |
| Portfolio                            | THUNDER X1®                               |
| Product Type                         | Modular jack                              |
| Product Series                       | EASY                                      |
| General Specifications               |   |
| ANSI/TIA Category                    | Cat 6A                                    |
| Cable Type                           | Unshielded                                |
| Conductor Type                       | Solid   Stranded                          |
| Transmission Standards               | ANSI/TIA-568.2-D   ISO/IEC 11801 Class EA |
| Wiring                               | T568A   T568B                             |
| Compatible Conductor Gauge, stranded | 26-24                                     |
| Termination Type                     | Tool Less                                 |
| Outlet Type                          | Standard                                  |
| Integrated Dust Cover Type           | Hinged                                    |
| Compatible Conductor Gauge, solid    | 24-22 AWG                                 |
| Color                                | Red                                       |
| Material Specifications              |   |
| Contact Plating Material             | Gold                                      |
| Material Type                        | Polycarbonate                             |
| Termination Contact Plating          | Tin                                       |
| Electrical Specifications            |   |
| Insulation Resistance, minimum       | 500 MOhm                                  |

|   |                                      |
|---|--------------------------------------|
| Dielectric Withstand Voltage, RMS, conductive surface | 1500 Vac at 60 Hz                    |
| Current Rating at Temperature                         | 1.5 A at 20 °C   1.5 A at 68 °F      |
| Contact Resistance, maximum                           | 100 mOhm                             |
| Contact Resistance Variation, maximum                 | 20 mOhm                              |
| <b>Environmental Specifications</b>                   |                                      |
| Operating Temperature                                 | -10 °C to +60 °C (+14 °F to +140 °F) |
| Flammability Rating                                   | UL 94 V-5                            |
| Storage Temperature                                   | -40 °C to +70 °C (-40 °F to +158 °F) |
| Safety Standard.                                      | UL   eTL                             |
| <b>Dimensions</b>                                     |                                      |
| Width   | 17                                   |
| Height.   | 19.2                                 |
| Depth.  | 38                                   |
| <b>Packing</b>  |                                      |
| Packaging quantity                                    | 1PC                                  |