

AMP CONNECT® THUNDER X10® Max Flex Keystone Module, UTP, Cat6A, Unshutterred, Angled, Yellow

MODEL NUMBER : **CMTHX10-FUUAYL**

Specifications :

Product Classification	
Regional Availability	Asia Europe Middle East Africa
Portfolio	THUNDER X1®
Product Type	Modular jack
Product Series	FLEX
General Specifications	
ANSI/TIA Category	Cat 6A
Cable Type	Unshielded
Conductor Type	Solid Stranded
Transmission Standards	ANSI/TIA-568.2-D ISO/IEC 11801 Class EA
Wiring	T568A T568B
Compatible Conductor Gauge, stranded	26–24
Termination Type	Punchdowns
Outlet Type	Angled
Integrated Dust Cover Type	NO
Compatible Conductor Gauge, solid	24–22 AWG
Color	Yellow.
Material Specifications	
Contact Plating Material	Gold
Material Type	Polycarbonate
Termination Contact Plating	Tin

Electrical Specifications	
Insulation Resistance, minimum	500 MOhm
Dielectric Withstand Voltage, RMS, conductive surface	1500 Vac at 60 Hz
Current Rating at Temperature	1.5 A at 20 °C 1.5 A at 68 °F
Contact Resistance, maximum	100 mOhm
Contact Resistance Variation, maximum	20 mOhm
Environmental Specifications	
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Flammability Rating	UL 94 V-4
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Safety Standard.	UL eTL
Dimensions	
Width	16.1
Height.	20.05
Depth.	38
Packing	
Packaging quantity	1PC