

OFYX™ Fiber optic cable Single-mode OS2, Outdoor, 288 core, Loose Tube, CM, Dielectric armour

MODEL NUMBER : FCOFYX-SM2L2DNS288F



Specifications :

Product Classification	
Regional Availability	Asia Europe Middle East Africa
Portfolio	OFYX®
Product Type	Fiber outdoor cable
Product Series	SM Fiber
General Specifications	
Subunit Type	Gel-free
Cable Type	Loose tube
Construction Type1	Dielectric Armour
Application	Duct
Cable Design	
Fiber Count	288
Number of ripcords	2 ripcords
Fibre colouring	Blue-orange-green-Brown-grey-white-red-black-yellow-violet-pink-turquoise
Fiber per tube	12F

Outer jacket colour	Black.
Outer jacket material	High Density Polyethylene (HDPE)
Tape	Water-swellable
Tensile strength elements and/or armouring	tape armour
Tube colour coding, layer 1	Blue. Orange. Green. Brown. Grey. White. Red. Black. Yellow. Violet. Pink. Turquoise
Mechanical Specifications	
Minimum Bend Radius, operation	148 mm
Nominal outer diameter	14.8 mm
Max. tensile strength for installation	2700 N
Crush resistance	1500 N/10 cm
Minimum Bend Radius, installation	296 mm
Optical Specifications	
Fibre category	OS2
Cable cutoff wavelength	1260 nm
Fibre name	OFYX
Fibre compliance	ITU-T G.652.D and ITU-T G.657.A1
Dispersion @ 1550 nm	18 nm
Dispersion @ 1625 nm	22 nm
Maximum Attenuation	0.34 dB/km / 0.34 dB/km / 0.20 dB/km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fibre Type	Single-mode
Environmental Specifications	
Temperature range, installation	-5 °C to 50 °C
Temperature range, operation	-20 °C to 60 °C
Temperature range, storage	-25 °C to 70 °C
Regulatory Compliance/Certifications	

ROHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	IEC 60794-3-11
Waterblocking	IEC 60794-1-2