

## 19" 1U (3+3) 6 WAY FRENCH TYPE NFC 61314 SOCKET 2 UNITS ON / OFF LIGHTED SWITCH, 3X1,5 mm<sup>2</sup> NYMHY CABLE, C20 PLUG ALUMINIUM PROFILE FRAME POWER DISTRIBUTION UNIT

MODEL NUMBER : **JH191206133**

### Specifications :

| Product Classification  |                                      |
|-------------------------|--------------------------------------|
| Regional Availability   | Asia   Europe   Middle East   Africa |
| Product Type            | Basic PDU                            |
| Product Series          | Note0                                |
| INPUT Characteristics   |                                      |
| PDU Input Voltage       | 220V AC - 250V AC                    |
| Maximum Input Amps      | 16A                                  |
| PDU Plug Type           | C20 Type Plug                        |
| Input Cord Length (m)   | 1.5                                  |
| Input Cord Length (ft.) | 5.                                   |
| Cable Specefications    | 3x1.5mm <sup>2</sup> NYMHY(16AWG)    |
| Protection Control      | Direct Connected                     |
| Control Function        | On-Off Switch                        |
| Input Phase             | Single Phase                         |
| OUTPUT Characteristics  |                                      |
| Output Load Capacity    | 250V AC 16A / 4kVA                   |
| Frequency Compatibility | 50 / 60 Hz                           |
| 1. Type of Sockets      | French Socket                        |
| 1. Sockets Qty.         | 3+3                                  |
| Cable Design            |                                      |

|                                      |                                 |
|--------------------------------------|---------------------------------|
| REACH Regulation                     | REACH Declaration               |
| Product Certifications               | CE                              |
| REACH Free of SVCH                   | Yes                             |
| EU RoHS Directive                    | Compliant   EU RoHS Declaration |
| Mercury Free                         | Yes.                            |
| China RoHS Regulation                | China RoHS Declaration          |
| Mechanical Specifications            |                                 |
| Rack Unit                            | 1U.                             |
| Mounting Position                    | Horizontal                      |
| Mounting Location                    | Front                           |
| Material & Colour                    | Aluminum Anodizing              |
| Depth                                | 44.45mm.                        |
| Height                               | 44.45mm                         |
| Weight                               | 1.00 Kg.                        |
| Widht                                | 482.6mm(19")                    |
| Environmental Specifications         |                                 |
| Operating Temperature                | 23 F° - 140 F° (-5C° - 60C°)    |
| Storage Temperature                  | -13 F° - 149 F° (-25C° - 65C°)  |
| Relative Humidity                    | %5 - %95                        |
| Operating Elevation (ft.)            | 0ft. - 100000ft.                |
| Regulatory Compliance/Certifications |                                 |
| RoHS Exemption Information           | Yes..                           |
| WEEE                                 | Note11                          |
| Standards                            | IEC 62368-1                     |
| Packing                              |                                 |
| Packaging quantity                   | 1PC                             |