

**19" 1U 8 WAY IEC320 C13 SOCKET SOCKET  
WITH CURRENT AND VOLTAGE DISPLAY ,  
3X1,5 mm² NYMHY CABLE, C20 PLUG  
ALUMINIUM PROFILE FRAME POWER  
DISTRIBUTION UNIT**

MODEL NUMBER : **JYH191408130**



**Specifications :**

| Product Classification  |                                      |
|-------------------------|--------------------------------------|
| Regional Availability   | Asia   Europe   Middle East   Africa |
| Product Type            | Basic PDU                            |
| Product Series          | Note0                                |
| INPUT Characteristics   |                                      |
| PDU Input Voltage       | 220V AC - 250V AC                    |
| Maximum Input Amps      | 16A                                  |
| PDU Plug Type           | C20 Type Plug                        |
| Input Cord Length (m)   | 1.5                                  |
| Input Cord Length (ft.) | 5.                                   |
| Cable Specefications    | 3x1.5mm² NYMHY(16AWG)                |
| Protection Control      | Direct Connected                     |

|                              |                                 |
|------------------------------|---------------------------------|
| Control Function             | Multimeter                      |
| Input Phase                  | Single Phase                    |
| OUTPUT Characteristics       |                                 |
| Output Load Capacity         | 250V AC 16A / 4kVA              |
| Frequency Compatibility      | 50 / 60 Hz                      |
| 1. Type of Sockets           | IEC320 C13 Socket               |
| 1. Sockets Qty.              | 8                               |
| Cable Design                 |                                 |
| REACH Regulation             | REACH Declaration               |
| Product Certifications       | CE                              |
| REACH Free of SVCH           | Yes                             |
| EU RoHS Directive            | Compliant   EU RoHS Declaration |
| Mercury Free                 | Yes.                            |
| China RoHS Regulation        | China RoHS Declaration          |
| Mechanical Specifications    |                                 |
| Rack Unit                    | 1U.                             |
| Mounting Position            | Horizontal                      |
| Mounting Location            | Front                           |
| Material & Colour            | Aluminum Anodizing              |
| Depth                        | 44.45mm.                        |
| Height                       | 44.45mm                         |
| Widht                        | 482.6mm(19")                    |
| Environmental Specifications |                                 |
| Operating Temperature        | 23 F° - 140 F° (-5C° - 60C°)    |
| Storage Temperature          | -13 F° - 149 F° (-25C° - 65C°)  |
| Relative Humidity            | %5 - %95                        |
| Operating Elevation (ft.)    | 0ft. - 100000ft.                |

| Regulatory Compliance/Certifications |             |
|--------------------------------------|-------------|
| RoHS Exemption Information           | Yes..       |
| WEEE                                 | Note11      |
| Standards                            | IEC 62368-1 |
| Packing                              |             |
| Packaging quantity                   | 1PC         |