19″ 2U 14 WAY GERMANY TYPE (DIN49440) SOCKET WITH CURRENT AND VOLTAGE DISPLAY , 3X1,5 mm² NYMHY CABLE, SCHUKO PLUG ALUMINIUM PROFILE FRAME POWER DISTRIBUTION UNIT

MODEL NUMBER : SH192114132

Specifications :

Product Classification	
Regional Availability	Asia | Europe | Middle East | Africa
Product Type	Basic PDU
Product Series	Note0
INPUT Characteristics	
PDU Input Voltage	220V AC - 250V AC
Maximum Input Amps	16A
PDU Plug Type	F Type Plug
Input Cord Length (m)	1.5
Input Cord Length (ft.)	5.
Cable Specefications	3x1.5mm² NYMHY(16AWG)
Protection Control	Miniature Circuit Breaker

Date :25/12/2025
AMP CONNECT® is a registered trademark

Control Function	Circuit Breaker
Input Phase	Single Phase
OUTPUT Characteristics	
Output Load Capacity	250V AC 16A / 4kVA
Frequency Compatibility	50 / 60 Hz
1. Type of Sockets	Schuko Socket
1. Sockets Qty.	14
Cable Design	
REACh Regulation	REACh Declaration
Product Certifications	CE
REACh Free of SVCH	Yes
EU RoHS Directive	Compliant | EU RoHS Declaration
Mercury Free	Yes.
China RoHS Regulation	China RoHS Declaration
Mechanical Specifications	
Rack Unit	2U.
Mounting Position	Horizontal
Mounting Location	Front
Material & Colour	Aluminum Anodizing
Depth	44.45mm.
Height	88.90mm
Weight	1.60 Kg.
Widht	482.6mm(19")
Environmental Specifications	
Operating Temperature	23 F° - 140 F° (-5C° - 60C°)
Storage Temperature	-13 F° - 149 F° (-25C° - 65C°)
Relative Humidity	%5 - %95

AMP CONNECT® is a registered trademark

Operating Elevation (ft.)	0ft. - 100000ft.
Regulatory Compliance/Certifications	
RoHS Exemption Information	Yes..
WEEE	Note11
Standards	IEC 62368-1
Packing	
Packaging quantity	1PC

Date :25/12/2025
AMP CONNECT® is a registered trademark