

## AMP CONNECT® THUNDER X1® Copper Patch cord Max Easy, UTP, Cat6, 24AWG, PVC,White, 2 Meter

MODEL NUMBER : **CCTHX1-UPE02WH**

### Specifications :

| Ürün sınıflandırması                 |   |
|--------------------------------------|---|
| Regional Availability                | Asia   Europe   Middle East   Africa , Asia   Europe   Middle East   Africa |
| Portfolio                            | THUNDER X1® , THUNDER X1®   |
| Product Type                         | Twisted pair patch cord , Twisted pair patch cord                           |
| Product Series                       | MAX EASY , MAX EASY   |
| Genel Özellikler                     |   |
| ANSI/TIA Category                    | Cat 6 , Cat 6   |
| Cable Type                           | U/UTP (unshielded) , U/UTP (unshielded)                                     |
| Jacket Color                         | White. , White.   |
| Conductor Type                       | Stranded , Stranded   |
| Transmission Standards               | IEEE 802.3bt Type 4 , IEEE 802.3bt Type 4                                   |
| Interface, Connector A               | RJ45 plug. , RJ45 plug.   |
| Interface, Connector B               | RJ45 plug , RJ45 plug   |
| Pairs Quantity                       | 4 Pairs , 4 Pairs   |
| Wiring                               | T568B , T568B   |
| Compatible Conductor Gauge, stranded | 24 AWG , 24 AWG   |
| Material Specifications              |   |
| Contact Plating Material             | Precious metals , Precious metals   |
| Material Type                        | Copper alloy   Polycarbonate , Copper alloy   Polycarbonate                 |
| Mechanical Specifications            |   |
| Plug Insertion Life, minimum         | 750 times , 750 times   |
| Plug Retention Force, minimum        | 133 N   29.9 lbf , 133 N   29.9 lbf   |
| Environmental Specifications         |   |

|   |   |
|---|---|
| Operating Temperature                       | -10 °C to +60 °C (+14 °F to +140 °F) , -10 °C to +60 °C (+14 °F to +140 °F)   |
| Environmental Space                         | Polyvinyl Chloride (PVC) , Polyvinyl Chloride (PVC)   |
| Flammability Rating                         | UL 94 V-2 , UL 94 V-2   |
| <b>Dimensions</b>                           |   |
| Diameter Over Jacket                        | 6.02 mm , 6.02 mm   |
| Cable Assembly Length (m)                   | 2 , 2   |
| Cable Assembly Length (ft)                  | 6.6 , 6.6   |
| <b>Regulatory Compliance/Certifications</b> |   |
| ISO 9001:2015                               | Designed - manufactured and/or distributed under this quality management system , Designed - manufactured and/or distributed under this quality management system |
| <b>Packing</b>                              |   |
| Packaging quantity                          | 1PC , 1PC   |