

AMP CONNECT® THUNDER X10® Max Easy Keystone Module, UTP, Cat6A, Shutterred, White

MODEL NUMBER : CMTHX10-EUSSWH

Specifications :

Ürün sınıflandırması	
Regional Availability	Asia Europe Middle East Africa
Portfolio	THUNDER X1®
Product Type	Modular jack
Product Series	EASY
Genel Özellikler	
ANSI/TIA Category	Cat 6A
Cable Type	Unshielded
Conductor Type	Solid Stranded
Transmission Standards	ANSI/TIA-568.2-D ISO/IEC 11801 Class EA
Wiring	T568A T568B
Compatible Conductor Gauge, stranded	26–24
Termination Type	Tool Less
Outlet Type	Standard
Integrated Dust Cover Type	Hinged
Compatible Conductor Gauge, solid	24–22 AWG
Color	White
Material Specifications	
Contact Plating Material	Gold
Material Type	Polycarbonate
Termination Contact Plating	Tin
Electrical Specifications	
Insulation Resistance, minimum	500 MOhm

Dielectric Withstand Voltage, RMS, conductive surface	1500 Vac at 60 Hz
Current Rating at Temperature	1.5 A at 20 °C 1.5 A at 68 °F
Contact Resistance, maximum	100 mOhm
Contact Resistance Variation, maximum	20 mOhm
Environmental Specifications	
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Flammability Rating	UL 94 V-1
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Safety Standard.	UL eTL
Dimensions	
Width	17
Height.	19.2
Depth.	38
Packing	
Packaging quantity	1PC