


## SPARX® Fiber optic cable Multi-mode OM4, Indoor/Outdoor, 6 core, Loose Tube, CMP, Non-Armoured

MODEL NUMBER : FCSPARX-M41L1NNS006F



### Specifications :

| Ürün sınıflandırması  |                                                             |
|-----------------------|-------------------------------------------------------------|
| Regional Availability | Asia   Europe   Middle East   Africa                        |
| Portfolio             | SPARX®                                                      |
| Product Type          | Fiber Indoor/Outdoor cable                                  |
| Product Series        | MM Fiber                                                    |
| Genel Özellikler      |                                                             |
| Subunit Type          | Gel-free                                                    |
| Flame Rating          | Plenum (OFNP)                                               |
| Cable Type            | Loose Tube                                                  |
| Construction Type1    | Non-armored                                                 |
| Application           | Duct   General Purpose Horizontal   Vertical Riser   Plenum |
| Cable Design          |                                                             |
| Fiber Count           | 6F                                                          |
| Number of ripcords    | 1 ripcord                                                   |
| Fibre colouring       | Blue-orange-green-brown-grey-white                          |
| Fiber per tube        | 6F                                                          |
| Outer jacket colour   | Aqua.                                                       |
| Central element       | Dielectric                                                  |

|                                             |                                                                                        |
|---------------------------------------------|----------------------------------------------------------------------------------------|
| Outer Jacket Material                       | Flame-Retardant   UV-Resistant                                                         |
| <b>Mechanical Specifications</b>            |                                                                                        |
| Minimum Bend Radius, operation              | 135 mm                                                                                 |
| Nominal outer diameter                      | 9.1 mm                                                                                 |
| Max. tensile strength for installation      | 2000 N                                                                                 |
| Crush resistance                            | 1500 N/10 cm                                                                           |
| Minimum Bend Radius, installation           | 160 mm                                                                                 |
| <b>Optical Specifications</b>               |                                                                                        |
| Fibre category                              | OM4                                                                                    |
| Maximum Attenuation                         | 3.0 dB/km / 1.0 dB/km                                                                  |
| Wavelengths                                 | 850 nm / 1300 nm                                                                       |
| Fibre Type                                  | Multimode                                                                              |
| Fiber Core Diameter                         | 50 µm                                                                                  |
| Minimum Effective Modal Bandwidth (EMB)     | 4700MHz/km                                                                             |
| Min. Overfilled Launch (OFL) Bandwidth      | 3500 MHz*km / 500 MHz*km                                                               |
| <b>Environmental Specifications</b>         |                                                                                        |
| Temperature range, installation             | 0 °C to 60 °C (32 °F to 140 °F )                                                       |
| Temperature range, operation                | -40 °C to 70 °C (-40 °F to 158 °F )                                                    |
| Temperature range, storage                  | -40 °C to 70 °C (-40 °F to 158 °F ).                                                   |
| <b>Regulatory Compliance/Certifications</b> |                                                                                        |
| Design and Test Criteria                    | ANSI/ICEA S-104-696   NFPA 262 (for plenum - riser and general building applications). |
| ROHS                                        | Free of hazardous substances according to RoHS 2011/65/EU                              |
| Approvals and Listings                      | National Electrical Code® (NEC®) OFNP   CSA FT-6                                       |