


## AMP Connect® Basic PDU Series, 20 C13 Socket, 6 C19 Socket, 1 Phase, 250V AC, 32A, 2x16A Magnetic Hydraulic Circuit Breaker, 3x4mm<sup>2</sup> 3.05m Cord, IEC309 Plug

MODEL NUMBER : **KBPV221110344**



AMP Connect® Basic PDU Series, 20 C13 Socket, 6 C19 Socket, 1 Phase,  
250V AC, 32A, 2x16A Magnetic Hydraulic Circuit Breaker, 3x4mm<sup>2</sup> 3.05m  
Cord, IEC309 Plug

### Specifications :

| ÇIKIŞ Özellikleri            |                                 |
|------------------------------|---------------------------------|
| Output Load Capacity         | 32A - 250V AC/8.000VA           |
| Genel Özellikler             |                                 |
| Color                        | Grey                            |
| Cable Design                 |                                 |
| REACH Regulation             | REACH Declaration               |
| Product Certifications       | RoSH                            |
| REACH Free of SVCH           | Yes                             |
| EU RoHS Directive            | Compliant   EU RoHS Declaration |
| Mercury Free                 | Yes.                            |
| China RoHS Regulation        | China RoHS Declaration          |
| Mechanical Specifications    |                                 |
| Mounting Position            | Vertical                        |
| Mounting Location            | Side                            |
| Depth                        | 44,45 mm                        |
| Height                       | 977,90 mm (22U)                 |
| Widht                        | 44,45 mm                        |
| Environmental Specifications |                                 |
| Relative Humidity            | %5 - %95                        |

| Regulatory Compliance/Certifications   |                                                                                                                              |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| RoHS Exemption Information             | Yes..                                                                                                                        |
| WEEE                                   | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Standards                              | CE                                                                                                                           |
| Uncategorized                          |                                                                                                                              |
| Main Input Voltage                     | 250V AC 1 Phase                                                                                                              |
| Product or Component Type              | PDU                                                                                                                          |
| PDU Type                               | Basic PDU                                                                                                                    |
| Main Output Voltage                    | 220V AC - 250V AC                                                                                                            |
| Input Connection Type                  | IEC60309 32A P + N + ( $\perp$ )                                                                                             |
| Number of Rack Unit                    | 0U                                                                                                                           |
| Cable Lenght                           | 2 MT 3x4 mm <sup>2</sup> H05VV-F                                                                                             |
| Breaker Type                           | 2x16A Miniature Circuit Breaker                                                                                              |
| Mounting Preference                    | No Preference                                                                                                                |
| Mounting Mode                          | Rack Mounted                                                                                                                 |
| Line Rated Current                     | 32A                                                                                                                          |
| Permissible Voltage                    | 220V AC - 250V AC                                                                                                            |
| Input Current Limits                   | 32A                                                                                                                          |
| Input Frequency                        | 50/60 Hz                                                                                                                     |
| Type and Number of the Sockets         | Schuko Socket   10                                                                                                           |
| Socket Security 1 - 2                  | Unlocked   Unlocked                                                                                                          |
| Ambient Air Temperature for Operations | 23 F° - 140 F° (-5C° - 60C°)                                                                                                 |
| Operating Altitude                     | 0ft. - 100000ft.                                                                                                             |
| Ambient Air Temperature for Storage    | -13 F° - 149 F° (-25C° - 65C°)                                                                                               |
| Storage Relative Humidity              | %5 - %95                                                                                                                     |
| Storage Altitude                       | 0ft. - 100000ft.                                                                                                             |
| Unit Type of Package                   | PCE                                                                                                                          |
| Number of Units in Package             | 1                                                                                                                            |
| Warranty                               | 2 Years Warranty                                                                                                             |

