

**OFYX™ Fiber optic cable Single-mode OS2,
Outdoor, 8 core, Single Tube, CM, Armoured,
Corrugated steel**

MODEL NUMBER : **FCOFYX-SM2S2ACS008F**



Specifications :

产品分类	
Regional Availability	Asia Europe Middle East Africa
Portfolio	OFYX®
Product Type	Fiber outdoor cable
Product Series	SM Fiber
一般规格	
Subunit Type	Gel-free
Cable Type	Single Tube
Construction Type1	Corrugated steel armour
Application	Direct Buried Duct
Environment	Outdoor
Cable Design	
Fiber Count	8
Number of ripcords	2 ripcords
Fibre colouring	Blue-orange-green-brown-grey-white
Fiber per tube	8F
Outer jacket colour	Black.
Outer jacket material	Linear Low Density Polyethylene (LLDPE)
Tape	Water-swellable

Tensile strength elements and/or armouring	Corrugated steel tape armour
Mechanical Specifications	
Minimum Bend Radius, operation	85 mm
Nominal outer diameter	8.5 mm
Max. tensile strength for installation	2700 N
Crush resistance	2000 N/10 cm
Minimum Bend Radius, installation	170 mm
Optical Specifications	
Fibre category	OS2
Cable cutoff wavelength	1260 nm
Fibre name	OFYX
Fibre compliance	ITU-T G.652.D and ITU-T G.657.A1
Dispersion @ 1550 nm	18 nm
Dispersion @ 1625 nm	22 nm
Maximum Attenuation	0.34 dB/km / 0.34 dB/km / 0.20 dB/km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fibre Type	Single-mode
Environmental Specifications	
Temperature range, installation	-5 °C to 50 °C
Temperature range, operation	-20 °C to 60 °C
Temperature range, storage	-25 °C to 70 °C
Regulatory Compliance/Certifications	
ROHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	IEC 60794-3-11
Waterblocking	IEC 60794-1-2