

## SPARX® Fiber Patch Cord Multi-Mode OM3/OMM SC/LC, UPC, LSZH, Duplex, 15 meter

MODEL NUMBER : **FPCSPARX-MMSLUD015**

### Specifications :

| 产品分类                                    |                                      |
|-----------------------------------------|--------------------------------------|
| Regional Availability                   | Asia   Europe   Middle East   Africa |
| Portfolio                               | SPARX®                               |
| Product Type                            | Fiber patch cord - Duplex            |
| Product Series                          | MM Fiber                             |
| 一般规格                                    |                                      |
| Flame Rating                            | Riser (OFNR)                         |
| Cable Type                              | Tight-Buffered                       |
| Jacket Color                            | Aqua..                               |
| Interface, Connector A                  | SC.                                  |
| Interface, Connector B                  | LC                                   |
| Boot Color                              | Aqua... , Aqua...                    |
| Housing Color                           | Aqua. , Aqua.                        |
| Cable Assembly Type                     | Two Fiber                            |
| Fiber Compliance                        | TIA 492AAAD                          |
| Optical Specifications                  |                                      |
| Maximum Attenuation                     | 2.8 dB/km / 1.0 dB/km                |
| Wavelengths                             | 850 nm / 1300 nm                     |
| Fiber Core Diameter                     | 50 µm                                |
| Minimum Effective Modal Bandwidth (EMB) | 4700MHz/km                           |
| Insertion Loss, Typical                 | 0.35 dB , 0.35 dB                    |
| Fiber Category                          | MM (OM3/OM4)                         |
| Specifications - Connector A            |                                      |

|                                             |                                                           |
|---------------------------------------------|-----------------------------------------------------------|
| Ferrule Material                            | Ceramic , Ceramic                                         |
| <b>Environmental Specifications</b>         |                                                           |
| Operating Temperature                       | -10 °C to +60 °C (+14 °F to +140 °F)                      |
| Environmental Space                         | LSZH/FRNC                                                 |
| Qualification Standards                     | IEC 60332-1   IEC 60332-3   IEC 60754   IEC 61034         |
| <b>Dimensions</b>                           |                                                           |
| Cable Assembly Length (m)                   | 15.                                                       |
| Cable Assembly Length (ft)                  | 50                                                        |
| <b>Regulatory Compliance/Certifications</b> |                                                           |
| ROHS                                        | Free of hazardous substances according to RoHS 2011/65/EU |
| CHINA-ROHS                                  | Below maximum concentration value                         |