

## 19" 2U 9 WAY BRITISH TYPE BS1363 SOCKET CIRCUIT BREAKER AND SURGE PROTECTION DEVICE CONNECTED, 3X1,5 mm<sup>2</sup> NYMHY CABLE, DIN49441 PLUG ALUMINIUM PROFILE FRAME POWER DISTRIBUTION UNIT

MODEL NUMBER : **SPH192309132**



### Specifications :

| 产品分类                    |                                                                             |
|-------------------------|-----------------------------------------------------------------------------|
| Regional Availability   | Asia   Europe   Middle East   Africa , Asia   Europe   Middle East   Africa |
| Product Type            | Basic PDU , Basic PDU                                                       |
| Product Series          | Note0 , Note0                                                               |
| INPUT Characteristics   |                                                                             |
| PDU Input Voltage       | 220V AC - 250V AC , 220V AC - 250V AC                                       |
| Maximum Input Amps      | 16A , 16A                                                                   |
| PDU Plug Type           | F Type Plug , F Type Plug                                                   |
| Input Cord Length (m)   | 1.5 , 1.5                                                                   |
| Input Cord Length (ft.) | 5. , 5.                                                                     |
| Cable Specefications    | 3x1.5mm <sup>2</sup> NYMHY(16AWG) , 3x1.5mm <sup>2</sup> NYMHY(16AWG)       |

|                              |                                                                   |
|------------------------------|-------------------------------------------------------------------|
| Protection Control           | SPD&MCB , SPD&MCB                                                 |
| Control Function             | SPD Light&Circuit Breaker , SPD Light&Circuit Breaker             |
| Input Phase                  | Single Phase , Single Phase                                       |
| 输出特性                         |                                                                   |
| Output Load Capacity         | 250V AC 16A / 4kVA , 250V AC 16A / 4kVA                           |
| Frequency Compatibility      | 50 / 60 Hz , 50 / 60 Hz                                           |
| 1. Type of Sockets           | BS1363 UK Socket , BS1363 UK Socket                               |
| 1. Sockets Qty.              | 9 , 9                                                             |
| Cable Design                 |                                                                   |
| REACH Regulation             | REACH Declaration , REACH Declaration                             |
| Product Certifications       | CE , CE                                                           |
| REACH Free of SVCH           | Yes , Yes                                                         |
| EU RoHS Directive            | Compliant   EU RoHS Declaration , Compliant   EU RoHS Declaration |
| Mercury Free                 | Yes. , Yes.                                                       |
| China RoHS Regulation        | China RoHS Declaration , China RoHS Declaration                   |
| Mechanical Specifications    |                                                                   |
| Rack Unit                    | 2U. , 2U.                                                         |
| Mounting Position            | Horizontal , Horizontal                                           |
| Mounting Location            | Front , Front                                                     |
| Material & Colour            | Aluminum Anodizing , Aluminum Anodizing                           |
| Depth                        | 44.45mm. , 44.45mm.                                               |
| Height                       | 88.90mm , 88.90mm                                                 |
| Widht                        | 482.6mm(19") , 482.6mm(19")                                       |
| Environmental Specifications |                                                                   |
| Operating Temperature        | 23 F° - 140 F° (-5C° - 60C°), 23 F° - 140 F° (-5C° - 60C°)        |
| Storage Temperature          | -13 F° - 149 F° (-25C° - 65C°), -13 F° - 149 F° (-25C° - 65C°)    |

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| Relative Humidity                    | %5 - %95 , %5 - %95                 |
| Operating Elevation (ft.)            | 0ft. - 100000ft. , 0ft. - 100000ft. |
| Regulatory Compliance/Certifications |                                     |
| RoHS Exemption Information           | Yes.. , Yes..                       |
| WEEE                                 | Note11 , Note11                     |
| Standards                            | IEC 62368-1 , IEC 62368-1           |
| Packing                              |                                     |
| Packaging quantity                   | 1PC , 1PC                           |